



# SEAL CLEAN KEYBOARD WITH SMART CARD READER

Model: SSKSV207RUSA

Seal Clean Waterproof Keyboards with a built-in tap-and-go RFID card reader from Seal Shield. Keyboards have a 100% waterproof & dishwasher-safe rating that is IP68-certified and designed to withstand industrial-grade disinfectants & cleaners. True type keyboard with tactile feel and full travel keys for smooth and natural typing. Features a Quick Connect Cable with RF shielding and a Seal Cap™ for easy plug-and-play. Built-in Contact Card Reader for added security supports all major smart cards, network log-in and single sign-on. Laser-etched keys stand up to frequent and vigorous cleaning. ABS plastic with stainless steel screws.

### **FEATURES:**



100% Waterproof, Dishwasher-Safe, & Fully Submersible



Gold Coated USB Quick Connect Cable, RF Shielding, & Seal Cap™ Protector



Full-Size Numeric Keypad, Laser Etched Keycaps



TAA Compliant



Standard Style Keyboard for Smooth Typing



Designed to Withstand Industrial-Grade Disinfectants & Cleaners



Built-In Contact (CAC) Card Reader



ABS Plastic Keyboard with Steel Screws is IP68-Certified



ABS Plastic with Stainless Steel Screws & Non-Corrosive Components



SSKSV207RUSA

#### ADVANCED CLEANING CAPABILITIES

· Dishwasher-Safe

Compatible with Spray & Wipe Disinfectant Products:

- · Clorox Healthcare®
- · Lysol®
- · PDI Products
- · Bleach, Ethanol, IPA, Quats, Citric Acid, & Hydrogen Peroxide, and Other Industrial-Grade Cleaners and Disinfectants





# SEAL CLEAN KEYBOARD WITH SMART CARD READER

Model: SSKSV207RUSA

### **TECHNICAL DATA:**

Compatibility: Windows®  Construction: ABS Plastic (Standard Style)  Key Layout: 104 US Language  Net Dimensions L x W x H: 18.07 x 6.85 x 1.38 in (45.9 x 17.4 x 3.5 cm)  Gross Dimensions L x W x H: 18.74 x 7.76 x 1.75 in (47.6 x 19.7 x 4.45 cm)  Net Weight: 2.02 lb (0.915 kg)  Gross Weight: 2.35 lb (1.065 kg)  Cable Length: 6 in (15cm) Quick Connect Cable with 6 ft
Key Layout:       104 US Language         Net Dimensions L x W x H:       18.07 x 6.85 x 1.38 in (45.9 x 17.4 x 3.5 cm)         Gross Dimensions L x W x H:       18.74 x 7.76 x 1.75 in (47.6 x 19.7 x 4.45 cm)         Net Weight:       2.02 lb (0.915 kg)         Gross Weight:       2.35 lb (1.065 kg)         Gable Length:       6 in (15cm) Quick Connect Cable with 6 ft
Net Dimensions L x W x H:       18.07 x 6.85 x 1.38 in (45.9 x 17.4 x 3.5 cm)         Gross Dimensions L x W x H:       18.74 x 7.76 x 1.75 in (47.6 x 19.7 x 4.45 cm)         Net Weight:       2.02 lb (0.915 kg)         Gross Weight:       2.35 lb (1.065 kg)         Gable Length:       6 in (15cm) Quick Connect Cable with 6 ft
Gross Dimensions L x W x H: 18.74 x 7.76 x 1.75 in (47.6 x 19.7 x 4.45 cm)  Net Weight: 2.02 lb (0.915 kg)  Gross Weight: 2.35 lb (1.065 kg)  Gable Length: 6 in (15cm) Quick Connect Cable with 6 ft
Net Weight:  2.02 lb (0.915 kg)  Gross Weight:  2.35 lb (1.065 kg)  6 in (15cm) Quick Connect Cable with 6 ft
Gross Weight: 2.35 lb (1.065 kg)  Gable Length: 6 in (15cm) Quick Connect Cable with 6 ft
Cable Length: 6 in (15cm) Quick Connect Cable with 6 ft
Cable Length: 6 in (15cm) Quick Connect Cable with 6 ft
Extension Cable
Connection Type: Gold Plated USB (can support PS/2 technology)
Supported Smart Cards: 5V, 3V and 1.8V, ISO/IEC 7816 Class A/B/C
Card Size: ID-1
Card Reader Speed: 12 Mbps (USB 2.0 full speed)
Card Reader Life Cycle: 100,000 Card Insertions
Key Switch Force: 53 ± 7 gf
Key Switch Life Cycle: Greater than 10 Million Keystrokes
Key Switch Type: Membrane Key Switch with Tactile Feedback
Keycaps Imaging Type: Laser Etched
Operating Current: 60mA
Total Key Travel: 4.0 ± 0.2 mm
Operating Voltage: 5VDC
Storage Temperature: -5° - 140° F (-20° to 60° C)
EMI - RFI: Conforms to FCC Rules for Class B Device
Waterproof/Dustproof Ratings: IP68, NEMA 4X
Approvals/Certifications: RoHS, WEEE, CE, FCC, WHQL, ICES-003, REACH, Cal Prop 65, TAA Compliant
Card Reader Compliance: ISO/IEC 7816, USB CCID, PC/SC, EMV 2008, GSA FIPS 201



Copyright© 2022, Seal Shield, LLC. All rights reserved. All other trademarks and trade names are those of their respective owners

Limited 2-Year Warranty